MMPC Model 10/20 (250-1640/41) Memory Management Faxback Doc. # 2529

Your System can accommodate the following types of memory:

Base RAM (conventional memory) - Memory below 640KB, which can be used by MS-DOS and all MS-DOS applications without requiring drivers.

Shadow RAM (upper memory area) - Memory from 640KB to 1024KB to (1(MB), which is used by the system BIOS, video BIOS, and other BIOS extensions.

Extended memory - Continuous memory above 1MB, which can be addressed directly by i486 microprocessors. Extended memory is often used for software disk caches, Ram disks, and software print spoolers. Extended memory can be directly used by many Windows and MS-DOS applications when you use the appropriate memory-related operating system features. Refer to your operating system documentation to learn more about using extended memory.

Extended memory - If you run programs that are designed to use expanded memory, you can use MS-DOS commands to enable your system to use expanded memory. Refer to your software documentation for more information on using expanded memory.

The following diagram illustrates the arrangement of memory in your computer:

67,108KB	r	7
or 52,428KB	1000000-3FFFFFF or 1000000-31FFFFF	Main Logic Board System RAM
16,384KB	100000-FFFFFF	Main Logic Board System DRAM or ISA Bus
1,024КВ 992КВ	0F8000-0FFFFF	Shadow DRAM Containing AT System BIOS
992KB 960KB	0F0000-0F7FFF	Shadow DRAM Containing System Setup Utility
900KB 896KB	0E0000-0EFFFF	Unused Not Available on ISA Bus
	0D0000-0CFFFF	
832KB	0C0000-0CFFFF	Shadow DRAM or ISA Bus
768KB	0A0000-0BFFFF	Video DRAM
640KB	00000-09FFFF	System DRAM
0KB -		

(smc-02/02/94)